

# Specifications.

## BMW X4.

### X4 xDrive20i.



BMW X4 xDrive20i		
<b>Body</b>		
No. of doors/seats		5 / 5
Length/width/height <sup>1)</sup> (unladen)	mm	4752 / 1918 / 1621
Wheelbase	mm	2864
Track, front/rear	mm	1620 / 1666
Turning circle	m	12.1
Tank capacity	approx. ltr	65
Engine oil <sup>2)</sup>	ltr	5.25
Weight, unladen, to DINEU	kg	1720 / 1795
Max. load to DIN	kg	680
Max. permissible weight	kg	2400
Max. axle load, front/rear	kg	1135 / 1370
Max. trailer load, braked (12%)/unbraked	kg	2400 / 750
Max. roof load/towbar download	kg	100 / 100
Luggage comp. capacity	ltr	525 – 1430
Air resistance	c <sub>d</sub> x A	0.30 x 2.59
<b>Engine</b>		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing
Effective capacity	cm <sup>3</sup>	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		min RON 91
Output	kW/hp	135 / 184
at	rpm	5000 – 6500
Torque	Nm	290
at	rpm	1350 – 4250
<b>Electrical System</b>		
Battery/Installation	Ah/-	92 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front		Aluminium double-joint tension-rod spring-strut axle
Suspension, rear		Five-link axle in lightweight steel construction
Brakes, front		Single-piston floating-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, Hill Descent Control, Performance Control, DSC linked to xDrive all-wheel drive; optional: Adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia- reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electric Power Steering (EPS), Variable Sport Steering with Servotronic function
Steering ratio, overall	:1	16.8
Tyres, front/rear		225/60 R18 104W XL
Rims, front/rear		7J x 18 light-alloy

<b>BMW X4 xDrive20i</b>			
<b>Transmission</b>			
Type of gearbox	8-speed Steptronic		
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	3.385
<b>Performance</b>			
Power-to-weight ratio (DIN)	kg/kW		12.7
Output per litre	kW/l		67.6
Acceleration 0–100 km/h	s		8.3
Top speed	km/h		215
<b>Off-road characteristics</b>			
Angle of approach/departure	°		25.0 / 21.9
Breakover angle	°		20.0
Ground clearance when unladen	mm		204
Fording depth (at 7 km/h)	mm		500
<b>BMW EfficientDynamics</b>			
BMW EfficientDynamics standard features	Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-controlled oil pump, efficiency- and weight-optimised all-wheel drive, differential and power divider with optimized-warm-up behavior, tyres with reduced roll resistance		
<b>Fuel consumption EU cycle</b>			
Urban	ltr/100 km		8.8 – 8.5
Extra-urban	ltr/100 km		6.5 – 6.3
Combined	ltr/100 km		7.3 – 7.1
CO <sub>2</sub>	g/km		168 – 163
Emission rating			EU6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change

The values for fuel consumption, CO<sub>2</sub> emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO<sub>2</sub>-emissions the CO<sub>2</sub> values may differ to the values stated here.

# BMW X4. X4 xDrive30i.

<b>BMW X4 xDrive30i</b>		
<b>Body</b>		
No. of doors/seats		5 / 5
Length/width/height <sup>1)</sup> (unladen)	mm	4752 / 1918 / 1621
Wheelbase	mm	2864
Track, front/rear	mm	1620 / 1666
Turning circle	m	12.1
Tank capacity	approx. ltr	65
Engine oil <sup>2)</sup>	ltr	5.25
Weight, unladen, to DINEU	kg	1720 / 1795
Max. load to DIN	kg	680
Max. permissible weight	kg	2400
Max. axle load, front/rear	kg	1135 / 1370
Max. trailer load, braked (12%)/unbraked	kg	2400 / 750
Max. roof load/towbar download	kg	100 / 100
Luggage comp. capacity	ltr	525 – 1430
Air resistance	c <sub>d</sub> x A	0.30 x 2.59
<b>Engine</b>		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing
Effective capacity	cm <sup>3</sup>	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	10.2
Fuel		min RON 91
Output	kW/hp	185 / 252
at	rpm	5200 – 6500
Torque	Nm	350
at	rpm	1450 – 4800
<b>Electrical System</b>		
Battery/Installation	Ah/–	92 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front		Aluminium double-joint tension-rod spring-strut axle
Suspension, rear		Five-link axle in lightweight steel construction
Brakes, front		Single-piston floating-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, Hill Descent Control, Performance Control DSC linked to xDrive all-wheel drive; optional: Adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia- reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electric Power Steering (EPS), Variable Sport Steering with Servotronic function
Steering ratio, overall	:1	16.8
Tyres, front/rear		225/60 R18 104W XL
Rims, front/rear		7J x 18 light-alloy

<b>BMW X4 xDrive30i</b>			
<b>Transmission</b>			
Type of gearbox	8-speed Steptronic		
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	3.385
<b>Performance</b>			
Power-to-weight ratio (DIN)	kg/kW		9.3
Output per litre	kW/l		92.6
Acceleration 0–100 km/h	s		6.3
Top speed	km/h		240
<b>Off-road characteristics</b>			
Angle of approach/departure	°		25.0 / 21.9
Breakover angle	°		20.0
Ground clearance when unladen	mm		204
Fording depth (at 7 km/h)	mm		500
<b>BMW EfficientDynamics</b>			
BMW EfficientDynamics standard features	Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-controlled oil pump, efficiency- and weight-optimised all-wheel drive, differential and power divider with optimized-warm-up behavior, tyres with reduced roll resistance		
<b>Fuel consumption EU cycle</b>			
Urban	ltr/100 km		8.5 – 8.4
Extra-urban	ltr/100 km		6.7 – 6.4
Combined	ltr/100 km		7.3 – 7.2
CO <sub>2</sub>	g/km		168 – 164
Emission rating			EU6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change

The values for fuel consumption, CO<sub>2</sub> emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO<sub>2</sub>-emissions the CO<sub>2</sub> values may differ to the values stated here.

# BMW X4. X4 M40i.

<b>BMW X4 M40i</b>		
<b>Body</b>		
No. of doors/seats		5 / 5
Length/width/height <sup>1)</sup> (unladen)	mm	4733 / 1938/ 1621
Wheelbase	mm	2864
Track, front/rear	mm	1615 / 1624
Turning circle	m	12.1
Tank capacity	approx. ltr	65
Engine oil <sup>2)</sup>	ltr	6.5
Weight, unladen, to DINEU	kg	1825 / 1900
Max. load to DIN	kg	600
Max. permissible weight	kg	2430
Max. axle load, front/rear	kg	1190 / 1375
Max. trailer load, braked (12%)/unbraked	kg	2000 / 750
Max. roof load/towbar download	kg	100 / 100
Luggage comp. capacity	ltr	525 – 1430
Air resistance	c <sub>d</sub> x A	0.30 x 2.59
<b>Engine</b>		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		M Performance TwinPower Turbo technology: TwinScroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing
Effective capacity	cm <sup>3</sup>	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		min RON 91
Output	kW/hp	260 / 354
at	rpm	5500 – 6500
Torque	Nm	500
at	rpm	1550 – 4500
<b>Electrical System</b>		
Battery/Installation	Ah/–	92 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front		Aluminium double-joint tension-rod spring-strut axle
Suspension, rear		Five-link axle in lightweight steel construction
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Twin-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, Hill Descent Control, Performance Control, M sport differential, DSC linked to xDrive all-wheel drive; optional: Adaptive M suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia- reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electric Power Steering (EPS), Variable Sport Steering with Servotronic function
Steering ratio, overall	:1	16.8
Tyres, front/rear		245/45 R20 103W XL / 275/40 R20 106W XL
Rims, front/rear		8J x 20 light-alloy / 9.5J x 20 light-alloy

<b>BMW X4 M40i</b>			
<b>Transmission</b>			
Type of gearbox	8-speed Steptronic		
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	3.385
<b>Performance</b>			
Power-to-weight ratio (DIN)	kg/kW		7.0
Output per litre	kW/l		86.7
Acceleration 0–100 km/h	s		4.8
Top speed	km/h		250
<b>Off-road characteristics</b>			
Angle of approach/departure	°		25.0 / 21.9
Breakover angle	°		20.0
Ground clearance when unladen	mm		204
Fording depth (at 7 km/h)	mm		500
<b>BMW EfficientDynamics</b>			
BMW EfficientDynamics standard features	Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-controlled oil pump, efficiency- and weight-optimised all-wheel drive, differential and power divider with optimized-warm-up behavior		
<b>Fuel consumption EU cycle</b>			
Urban	ltr/100 km		11.5 – 11.3
Extra-urban	ltr/100 km		7.7 – 7.6
Combined	ltr/100 km		9.1 – 9.0
CO <sub>2</sub>	g/km		206 – 205
Emission rating			EU6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

- <sup>1)</sup> Height including roof aerial  
<sup>2)</sup> Oil change

The values for fuel consumption, CO<sub>2</sub> emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO<sub>2</sub>-emissions the CO<sub>2</sub> values may differ to the values stated here.

# BMW X4. X4 xDrive20d.

<b>BMW X4 xDrive20d</b>		
<b>Body</b>		
No. of doors/seats		5 / 5
Length/width/height <sup>1)</sup> (unladen)	mm	4752 / 1918 / 1621
Wheelbase	mm	2864
Track, front/rear	mm	1620 / 1666
Turning circle	m	12.1
Tank capacity	approx. ltr	68
Engine oil <sup>2)</sup>	ltr	5.0
Weight, unladen, to DINEU	kg	1740 / 1815
Max. load to DIN	kg	640
Max. permissible weight	kg	2400
Max. axle load, front/rear	kg	1160 / 1395
Max. trailer load, braked (12%)/unbraked	kg	2400 / 750
Max. roof load/towbar download	kg	100 / 100
Luggage comp. capacity	ltr	525 – 1430
Air resistance	$c_d \times A$	0.30 x 2.59
<b>Engine</b>		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: turbocharger with variable inlet geometry, common rail direct fuel injection with solenoid injectors, maximum injection pressure 2000 bar
Effective capacity	cm <sup>3</sup>	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	140 / 190
at	rpm	4000
Torque	Nm	400
at	rpm	1750 – 2500
<b>Electrical System</b>		
Battery/Installation	Ah/–	92 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front		Aluminium double-joint tension-rod spring-strut axle
Suspension, rear		Five-link axle in lightweight steel construction
Brakes, front		Single-piston floating-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, Hill Descent Control, Performance Control, DSC linked to xDrive all-wheel drive; optional: Adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electric Power Steering (EPS), Variable Sport Steering with Servotronic function
Steering ratio, overall	:1	16.8
Tyres, front/rear		225/60 R18 104W XL
Rims, front/rear		7J x 18 light-alloy

<b>BMW X4 xDrive20d</b>			
<b>Transmission</b>			
Type of gearbox	8-speed Steptronic		
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	3.231
<b>Performance</b>			
Power-to-weight ratio (DIN)	kg/kW		12.4
Output per litre	kW/l		70.2
Acceleration 0–100 km/h	s		8.0
Top speed	km/h		213
<b>Off-road characteristics</b>			
Angle of approach/departure	°		25.0 / 21.9
Breakover angle	°		20.0
Ground clearance when unladen	mm		204
Fording depth (at 7 km/h)	mm		500
<b>BMW EfficientDynamics</b>			
BMW EfficientDynamics standard features	Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-controlled oil pump, efficiency- and weight-optimised all-wheel drive, differential and power divider with optimized-warm-up behavior, tyres with reduced roll resistance, BMW Blue Performance technology including SCR catalytic converter		
<b>Fuel consumption EU cycle</b>			
Urban	ltr/100 km		6.3 – 5.9
Extra-urban	ltr/100 km		5.3 – 5.1
Combined	ltr/100 km		5.6 – 5.4
CO <sub>2</sub>	g/km		149 – 142
Emission rating			EU6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change

The values for fuel consumption, CO<sub>2</sub> emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO<sub>2</sub>-emissions the CO<sub>2</sub> values may differ to the values stated here.



# BMW X4. X4 xDrive25d.

<b>BMW X4 xDrive25d</b>		
<b>Body</b>		
No. of doors/seats		5 / 5
Length/width/height <sup>1)</sup> (unladen)	mm	4752 / 1918 / 1621
Wheelbase	mm	2864
Track, front/rear	mm	1620 / 1666
Turning circle	m	12.1
Tank capacity	approx. ltr	68
Engine oil <sup>2)</sup>	ltr	5.0
Weight, unladen, to DINEU	kg	1755 / 1830
Max. load to DIN	kg	640
Max. permissible weight	kg	2420
Max. axle load, front/rear	kg	1145 / 1400
Max. trailer load, braked (12%)/unbraked	kg	2400 / 750
Max. roof load/towbar download	kg	100 / 100
Luggage comp. capacity	ltr	525 – 1430
Air resistance	c <sub>d</sub> x A	0.30 x 2.59
<b>Engine</b>		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: multi-stage charging, high and low pressure turbocharger with variable-geometry, Common Rail direct injection with solenoid valve injectors (max. injection pressure: 2500 bar)
Effective capacity	cm <sup>3</sup>	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	170 / 231
at	rpm	4400
Torque	Nm	500
at	rpm	2000
<b>Electrical System</b>		
Battery/Installation	Ah/–	92 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front		Aluminium double-joint tension-rod spring-strut axle
Suspension, rear		Five-link axle in lightweight steel construction
Brakes, front		Single-piston floating-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, Hill Descent Control, Performance Control, DSC linked to xDrive all-wheel drive; optional: Adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electric Power Steering (EPS), Variable Sport Steering with Servotronic function
Steering ratio, overall	:1	16.8
Tyres, front/rear		225/60 R18 104W XL
Rims, front/rear		7J x 18 light-alloy

<b>BMW X4 xDrive25d</b>			
<b>Transmission</b>			
Type of gearbox	8-speed Steptronic		
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	3.231
<b>Performance</b>			
Power-to-weight ratio (DIN)	kg/kW		10.3
Output per litre	kW/l		85.2
Acceleration 0–100 km/h	s		6.8
Top speed	km/h		230
<b>Off-road characteristics</b>			
Angle of approach/departure	°		25.0 / 21.9
Breakover angle	°		20.0
Ground clearance when unladen	mm		204
Fording depth (at 7 km/h)	mm		500
<b>BMW EfficientDynamics</b>			
BMW EfficientDynamics standard features	Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-controlled oil pump, efficiency- and weight-optimised all-wheel drive, differential and power divider with optimized-warm-up behavior, tyres with reduced roll resistance, BMW Blue Performance technology including SCR catalytic converter		
<b>Fuel consumption EU cycle</b>			
Urban	ltr/100 km		6.3 – 6.2
Extra-urban	ltr/100 km		5.3 – 5.1
Combined	ltr/100 km		5.7 – 5.5
CO <sub>2</sub>	g/km		149 – 145
Emission rating			EU6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change

The values for fuel consumption, CO<sub>2</sub> emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO<sub>2</sub>-emissions the CO<sub>2</sub> values may differ to the values stated here.

# BMW X4. X4 xDrive30d.

<b>BMW X4 xDrive30d</b>		
<b>Body</b>		
No. of doors/seats		5 / 5
Length/width/height <sup>1)</sup> (unladen)	mm	4752 / 1918 / 1621
Wheelbase	mm	2864
Track, front/rear	mm	1620 / 1666
Turning circle	m	12.1
Tank capacity	approx. ltr	68
Engine oil <sup>2)</sup>	ltr	6.5
Weight, unladen, to DINEU	kg	1820 / 1895
Max. load to DIN	kg	640
Max. permissible weight	kg	2460
Max. axle load, front/rear	kg	1195 / 1415
Max. trailer load, braked (12%)/unbraked	kg	2400 / 750
Max. roof load/towbar download	kg	100 / 100
Luggage comp. capacity	ltr	525 – 1430
Air resistance	c <sub>d</sub> x A	0.30 x 2.59
<b>Engine</b>		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: turbocharger with variable-geometry, Common Rail direct injection with piezo injectors (max. injection pressure: 2500 bar)
Effective capacity	cm <sup>3</sup>	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	195 / 265
at	rpm	4000
Torque	Nm	620
at	rpm	2000 – 2500
<b>Electrical System</b>		
Battery/Installation	Ah/–	92 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front		Aluminium double-joint tension-rod spring-strut axle
Suspension, rear		Five-link axle in lightweight steel construction
Brakes, front		Single-piston floating-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, Hill Descent Control, Performance Control, DSC linked to xDrive all-wheel drive; optional: Adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia- reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electric Power Steering (EPS), Variable Sport Steering with Servotronic function
Steering ratio, overall	:1	16.8
Tyres, front/rear		225/60 R18 104W XL
Rims, front/rear		7J x 18 light-alloy

<b>BMW X4 xDrive30d</b>			
<b>Transmission</b>			
Type of gearbox	8-speed Steptronic		
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.313
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.478
Final drive		:1	2.813
<b>Performance</b>			
Power-to-weight ratio (DIN)	kg/kW		9.3
Output per litre	kW/l		65.2
Acceleration 0–100 km/h	s		5.8
Top speed	km/h		240
<b>Off-road characteristics</b>			
Angle of approach/departure	°		25.0 / 21.9
Breakover angle	°		20.0
Ground clearance when unladen	mm		204
Fording depth (at 7 km/h)	mm		500
<b>BMW EfficientDynamics</b>			
BMW EfficientDynamics standard features	Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-controlled oil pump, efficiency- and weight-optimised all-wheel drive, differential and power divider with optimized-warm-up behavior, tyres with reduced roll resistance, BMW Blue Performance technology including SCR catalytic converter		
<b>Fuel consumption EU cycle</b>			
Urban	ltr/100 km		6.9 – 6.7
Extra-urban	ltr/100 km		5.5 – 5.4
Combined	ltr/100 km		6.0 – 5.8
CO <sub>2</sub>	g/km		158 – 153
Emission rating			EU6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change

The values for fuel consumption, CO<sub>2</sub> emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO<sub>2</sub>-emissions the CO<sub>2</sub> values may differ to the values stated here.

# BMW X4. X4 M40d.

<b>BMW X4 M40d</b>		
<b>Body</b>		
No. of doors/seats		5 / 5
Length/width/height <sup>1)</sup> (unladen)	mm	4733 / 1938 / 1621
Wheelbase	mm	2864
Track, front/rear	mm	1615 / 1624
Turning circle	m	12.1
Tank capacity	approx. ltr	68
Engine oil <sup>2)</sup>	ltr	6.5
Weight, unladen, to DINEU	kg	1895 / 1970
Max. load to DIN	kg	600
Max. permissible weight	kg	2525
Max. axle load, front/rear	kg	1220 / 1425
Max. trailer load, braked (12%)/unbraked	kg	2400 / 750
Max. roof load/towbar download	kg	100 / 100
Luggage comp. capacity	ltr	525 – 1430
Air resistance	c <sub>d</sub> x A	0.32 x 2.59
<b>Engine</b>		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		M Performance TwinPower Turbo technology: multi-stage charging, high and low pressure turbocharger with variable-geometry, Common Rail direct injection with piezo injectors (max. injection pressure: 2500 bar)
Effective capacity	cm <sup>3</sup>	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	240 / 326
at	rpm	4400
Torque	Nm	680
at	rpm	1750 – 2750
<b>Electrical System</b>		
Battery/Installation	Ah/–	92 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front		Aluminium double-joint tension-rod spring-strut axle
Suspension, rear		Five-link axle in lightweight steel construction
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Twin-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, Hill Descent Control, Performance Control, M sport differential, DSC linked to xDrive all-wheel drive; optional: Adaptive M suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia- reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electric Power Steering (EPS), Variable Sport Steering with Servotronic function
Steering ratio, overall	:1	16.8
Tyres, front/rear		245/45 R20 103W XL / 275/40 R20 106W XL
Rims, front/rear		8J x 20 light-alloy / 9.5J x 20 light-alloy

<b>BMW X4 M40d</b>			
<b>Transmission</b>			
Type of gearbox	8-speed Steptronic		
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.313
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.478
Final drive		:1	2.813
<b>Performance</b>			
Power-to-weight ratio (DIN)	kg/kW		7.9
Output per litre	kW/l		80.2
Acceleration 0–100 km/h	s		4.9
Top speed	km/h		250
<b>Off-road characteristics</b>			
Angle of approach/departure	°		25.0 / 21.9
Breakover angle	°		20.0
Ground clearance when unladen	mm		204
Fording depth (at 7 km/h)	mm		500
<b>BMW EfficientDynamics</b>			
BMW EfficientDynamics standard features	Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-controlled oil pump, efficiency- and weight-optimised all-wheel drive, differential and power divider with optimized-warm-up behavior, BMW Blue Performance technology including SCR catalytic converter		
<b>Fuel consumption EU cycle</b>			
Urban	ltr/100 km		7.3 – 7.2
Extra-urban	ltr/100 km		6.3 – 5.9
Combined	ltr/100 km		6.6 – 6.4
CO <sub>2</sub>	g/km		173 – 170
Emission rating			EU6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change

The values for fuel consumption, CO<sub>2</sub> emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO<sub>2</sub>-emissions the CO<sub>2</sub> values may differ to the values stated here.