## The BMW M3 Sedan. M3 Competition.

		BMW M3 Competition Sedan	
Body		415	
No of doors/seats		4/5	
Length/width/height (unladen)	mm	4794 / 1903 / 1433	
Wheelbase	mm	2857	
Track, front/rear	mm	1617 / 1605	
Ground clearance	mm	120	
Turning circle	m	12.2	
Fuel tank capacity	approx. I	59	
Engine oil 1)	1 .	7.0	
Weight, unladen, to DIN/EU	kg	1730 / 1805	
Max load to DIN	kg	480	
Max permissible weight	kg	2210	
Max axle load, front/rear	kg	1080 / 1180	
Max trailer load, braked (12%)/unbraked	kg	-/- 75/-	
Max roofload/max towbar download	kg	75 / –	
Luggage comp capacity	I	480	
Air resistance	c <sub>d</sub> x A	0.33 x 2.34	
Power Unit			
Config/No of cyls/valves		In-line / 6 / 4	
Engine technology	(m	M TwinPower Turbo technology with two mono-scroll turbochargers, indirect charge air cooling, High Precision Injection aximum injection pressure: 350 bar), VALVETRONIC fully variable valve timing Double-VANOS variable camshaft timing	
Effective capacity	CC	2993	
Stroke/bore		90.0 / 84.0	
	mm :1	9.3	
Compression ratio	- 11	<u> </u>	
Fuel May autout	Id M//bro	RON 98 (min. RON 91)	
Max output	kW/hp	375 / 510 6250	
May targue	rpm	650	
Max torque	Nm		
at	rpm	2750 – 5500	
Electrical System			
Battery/installation	Ah/-	70 / luggage compartment	
Driving Dynamics and Safe	ty		
Suspension, front		Adaptive M suspension with double-joint spring strut axle in lightweight aluminium construction, M-specific kinematics and elastokinematics	
Suspension, rear		Adaptive M suspension with five-link axle in lightweight aluminium/steel	
Caoperiolori, real	construction, rear-axle subframe with rigid bolted connection to the body,  M-specific kinematics and elastokinematics		
Brakes, front		M Compound brakes, vented, with six-piston fixed callipers	
Brakes, rear		M Compound brakes, vented, with single-piston floating callipers	
Driving stability systems	5	Standard: DSC incl. ABS, ASC and M Dynamic Mode (MDM), can be switched off, integrated wheel slip limitation, CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Start-Off Assistant, Active M Differential,	
Safety equipment	ţ	tandard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelts on all seats with belt stopper, belt tensioner and belt force limiter at the front, crash sensors, tyre pressure indicator	
Steering	E	lectric Power Steering (EPS) with M-specific Servotronic function and variable sport ratio	
Steering ratio, overall	:1	15.0	
Tyres, front/rear		275/40 ZR18 103Y XL 285/35 ZR19 103Y XL	
Rims, front/rear		9.5J x 18 light-alloy	

			BMW M3 Competition Sedan
Transmission			5'11 IMO: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Type of transm			Eight-speed M Steptronic transmission with Drivelogic
Gear ratios	1	:1	5.000
	<u>II</u>	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.313
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.478
Final drive		:1	3.154
Performance			
Power-to-weigh	ht ratio (DIN)	kg/kW	4.6
Output per litre		kW/l	125.3
Acceleration	0-100 km/h	S	3.9
Acceleration	80-120 km/h		
in 4th/5th gear		S	2.6 / 3.4
Top speed		km/h	250 / 290 <sup>2)</sup>
BMW Efficien	tDynamics		
BMW Efficient[	Dynamics		Brake Energy Regeneration, Electric Power Steering,
standard featur	es		Auto Start Stop function, Optimum Shift Indicator in manual shift mode,
			BMW EfficientLightweight, on-demand operation of ancillary units, map-
			regulated oil pump, rear differential with optimised efficiency, Li-ion battery,
			optimised aerodynamic attributes
			·
Fuel Consum	ption ECE		
with standard to	•		
Urban		l/100 km	14.6
Extra-urban		l/100 km	7.6
Combined		l/100 km	10,2
CO <sub>2</sub>		g/km	234
Emission rating		9	Euro 6d
Liniooloritating	1		25.000

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

The fuel consumption,  $CO_2$  emission and electric power consumption figures are determined according to the European Regulation (EC) 2007/715 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO2 emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO2-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO2 emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

<sup>&</sup>lt;sup>1)</sup> Oil change with filter <sup>2)</sup> Limited / with optional M Driver's Package

BMW Media Information 09/2020 Page 3

## Exterior and interior dimensions. The BMW M3 Sedan. M3.



