

		MINI One Countryman	MINI One Countryman	MINI Cooper Countryman	MINI Cooper Countryman	MINI Cooper S Countryman	MINI Cooper S Countryman	MINI Cooper S Countryman ALL4	MINI Cooper S Countryman ALL4
Engine Platform		N16B16U0	N16B16U0	N16B16M0	N16B16M0	N18B16M0	N18B16M0	N18B16M0	N18B16M0
Transmission		M6	A6	M6	A6	M5	A5	M6	A6
No of doors / seats	-	5 / 5	5 / 5	5 / 5	5 / 5	5 / 5	5 / 5	5 / 5	5 / 5
Vehicle Length / Width / Height (with antenna) -unloaded-	mm	4097 / 1789 / 1561 (1579)	4097 / 1789 / 1561 (1579)	4097 / 1789 / 1561 (1579)	4097 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)
Wheelbase / Turning Circle	mm / m	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6
Wheel Offset	mm	46 / 46	46 / 46	46 / 46	46 / 46	50 / 50	50 / 50	50 / 50	50 / 50
Track Front / Rear	mm	1534 / 1559	1534 / 1559	1534 / 1559	1534 / 1559	1525 / 1551	1525 / 1551	1525 / 1551	1525 / 1551
Overhang Front / Rear	mm	764 / 738	764 / 738	764 / 738	764 / 738	770 / 745	770 / 745	770 / 745	770 / 745
Ground Clearance -empty-	mm	149	149	149	149	149	149	149	149
Shoulder Width Front / Rear	mm	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323
Elbow Width Front / Rear	mm	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360
Eff. Head Room Front / Rear	mm	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953
Luggage Capacity	ltr	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170
Fuel Tank Capacity	ltr	47	47	47	47	47	47	47	47
Curb Weight -acc DIN-	kg	1265 / 1340	1295 / 1370	1265 / 1340	1295 / 1370	1310 / 1385	1335 / 1410	1380 / 1455	1405 / 1480
Axle Load Ratio -unloaded DIN-	%	41.1	40.2	41.1	40.2	39.7	39	40.9	40.2
Gross Vehicle Weight / payload	kg	1735 / 470	1765 / 470	1735 / 470	1765 / 470	1780 / 470	1805 / 470	1840 / 460	1865 / 460
Axle Load Limit Front / Rear	kg	935 / 855	965 / 855	930 / 855	960 / 855	960 / 855	980 / 855	980 / 895	1000 / 895
Trailer Load Braked -12% / 8%-	kg	/	/	/	1000 / 1000	750 / 750	1000 / 1000	750 / 750	1000 / 1000
Trailer Load Unbraked -nose weight	kg	/	/	/	500 / 75	500 / 75	500 / 75	500 / 75	500 / 75
Gross vehicle weight -trailer towing-	kg	1840	1880	1840	1880	1855	1880	1915	1940
Rear axle load limit -trailer towing-	kg	959	959	959	959	959	959	997	997
Roof load	kg	75	75	75	75	75	75	75	75
Engine Type / Cylinders / Valves per Cylinder	-	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4
Fuel Management	-	MEV 1722	MEV 1722	MEV 1722	MEV 1722	MEVD 1722	MEVD 1722	MEVD 1722	MEVD 1722
Effective Displacement	cm ³	1598	1598	1598	1598	1598	1598	1598	1598
Stroke / Bore	mm	85.8 / 77.0	85.8 / 77.0	85.8 / 77.0	85.8 / 77.0	85.8 / 77.0	85.8 / 77.0	85.8 / 77.0	85.8 / 77.0
Nominal Power Output / Engine Speed	hp (kW) / 1/min	98 (72) / 6000	98 (72) / 6000	122 (90) / 6000	122 (90) / 6000	184 (135) / 5500	184 (135) / 5500	184 (135) / 5500	184 (135) / 5500
Max Torque / Engine Speed	Nm / 1/min	153 / 3000	153 / 3000	160 / 4250	160 / 4250	240 / 1600-5000 (Overboost: 260 /1700-4500)	240 / 1600-5000 (Overboost: 260 /1700-4500)	240 / 1600-5000 (Overboost: 260 /1700-4500)	240 / 1600-5000 (Overboost: 260 /1700-4500)
Compression Ratio / Fuel Type	-	11.0 / RON 91-98	11.0 / RON 91-98	11.0 / RON 91-98	11.0 / RON 91-98	10.5 / RON 91-98	10.5 / RON 91-98	10.5 / RON 91-98	10.5 / RON 91-98
Exhaust Emissions Classification	-	EUS	EUS	EUS	EUS	EUS	EUS	EUS	EUS
Gearbox Reference Code	-	G255	AW 260K	G255	AW 260K	G255 TŮ	AW 225K	G253 TŮ	AW 225K
Gear Ratio 1st / 2nd / 3rd	-	3.214 / 1.792 / 1.194	4.148 / 2.37 / 1.566	3.214 / 1.792 / 1.194	4.148 / 2.37 / 1.556	3.308 / 2.13 / 1.483	4.044 / 2.371 / 1.556	3.308 / 2.13 / 1.483	4.044 / 2.371 / 1.556
Gear Ratio 4th / 5th / 6th	-	0.914 / 0.784 / 0.683	1.155 / 0.859 / 0.686	1.155 / 0.784 / 0.683	1.155 / 0.859 / 0.686	1.139 / 0.949 / 0.816	1.159 / 0.852 / 0.672	1.159 / 0.949 / 0.816	1.159 / 0.852 / 0.672
Reverse Ratio	-	3.143	3.394	3.143	3.394	3.231	3.193	3.231	3.193
Final Drive Ratio	-	4.353	4.643	4.722	4.643	3.706	3.683	3.706	3.683
Steering Type / Ratio	-	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1
Brake Front / Diameter	- / mm	Ventilated Disc / 294	Ventilated Disc / 294	Ventilated Disc / 294	Ventilated Disc / 294	Ventilated Disc / 307	Ventilated Disc / 307	Ventilated Disc / 307	Ventilated Disc / 307
Brake Rear / Diameter	- / mm	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280
Drag Cd / A / Cd x A	- / m ² / m ²	0.36 / 2.36 / 0.85	0.36 / 2.36 / 0.85	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.36 / 2.36 / 0.85	0.36 / 2.36 / 0.85	0.36 / 2.36 / 0.85	0.36 / 2.36 / 0.85
Top Speed	mph / km/h	107 / 175	104 / 168	118 / 190	113 / 182	134 / 215	130 / 210	130 / 210	127 / 205
Acceleration 0-62mph (0-100km/h)	s	11.9	13.9	10.5	11.6	7.6	7.9	8.3	8.3
Acceleration 0-1000m	s	33.7	36.1	32.2	33.3	28.2	28.5	29	29
Acceleration 50-75mph (80-120km/h) 4th / 5th	s	13.9 / 17.9	- / -	11.6 / 14.9	- / -	7.1 / 8.6	7.2 / 9.4	- / -	- / -
Output Per Litre	kW/ltr	45.1	45.1	56.3	56.3	84.5	84.5	84.5	84.5
Weight Ratio	kg/kW	17.6	18	14.1	14.4	9.7	9.9	10.2	10.4
Fuel Consumption -urban-	mpg / l/100km	38.2 / 7.4	30.4 / 9.3	38.2 / 7.4	30.4 / 9.3	37.7 / 7.5	29.7 / 9.5	34.4 / 8.2	27.4 / 10.3
Fuel Consumption -extra urban-	mpg / l/100km	54.3 / 5.2	47.1 / 6.0	54.3 / 5.2	47.1 / 6.0	52.3 / 5.4	49.6 / 5.7	45.6 / 5.8	45.6 / 6.2
Fuel Consumption -combined-	mpg / l/100km	47.1 / 6.0	39.2 / 7.2	47.1 / 6.0	39.2 / 7.2	46.3 / 6.1	39.8 / 7.1	42.2 / 6.7	36.7 / 7.7
Range at Fuel Consumption-combined-	miles / km	488 / 785	407 / 655	488 / 785	407 / 655	478 / 770	401 / 660	435 / 700	379 / 610
CO ₂ Emissions -EU-	g/km	139	168	140	168	143	166	157	180
Tyre Size -front-	-	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V
Tyre Size -rear-	-	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V
Wheel Size -front-	-	6.5J x 16 Steel Wheel	6.5J x 16 Steel Wheel	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy
Wheel Size -rear-	-	6.5J x 16 Steel Wheel	6.5J x 16 Steel Wheel	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy
Radiator incl. Heater Capacity	ltr	5.5	6	5.5	6	5.5	6	5.5	6
Engine Oil Replacement Capacity	ltr	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
Gearbox Fluid Replacement Capacity	ltr	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent
Battery Capacity / Installed Position	Ah / -	60 / Engine Bay	55 / Engine Bay	60 / Engine Bay	55 / Engine Bay	60 / Engine Bay	55 / Engine Bay	70 / Engine Bay	55 / Engine Bay
Alternator Output rating	A/W	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100

		MINI One D Countryman	MINI Cooper D Countryman	MINI Cooper D Countryman	MINI Cooper D Countryman ALL4	MINI Cooper D Countryman ALL4	MINI Cooper SD Countryman	MINI Cooper SD Countryman	MINI Cooper SD Countryman ALL4	MINI Cooper SD Countryman ALL4
Engine Platform		N47C16K1	N47C16U1	N47C20K1	N47C16U1	N47C20K1	N47C20U1	N47C20U1	N47C20U1	N47C20U1
Transmission		M6	M6	A6	M6	A6	M6	A6	M6	A6
No of doors / seats	-	5/5	5/5	5/5	5/5	5/5	5/5	5/5	5/5	5/5
Vehicle Length / Width / Height (with antenna) -unloaded-	mm	4097 / 1789 / 1561 (1579)	4097 / 1789 / 1561 (1579)	4097 / 1789 / 1561 (1579)	4097 / 1789 / 1561 (1579)	4097 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)	4110 / 1789 / 1561 (1579)
Wheelbase / Turning Circle	mm / m	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6	2595 / 11.6
Wheel Offset	mm	46 / 46	46 / 46	46 / 46	46 / 46	46 / 46	50 / 50	50 / 50	50 / 50	50 / 50
Track Front / Rear	mm	1534 / 1559	1534 / 1559	1534 / 1559	1534 / 1559	1534 / 1559	1525 / 1551	1525 / 1551	1525 / 1551	1525 / 1551
Overhang Front / Rear	mm	764 / 738	764 / 738	764 / 738	764 / 738	764 / 738	770 / 745	770 / 745	770 / 745	770 / 745
Ground Clearance -empty-	mm	149	149	149	149	149	149	149	149	149
Shoulder Width Front / Rear	mm	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323	1341 / 1323
Elbow Width Front / Rear	mm	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360	1378 / 1360
Eff. Head Room Front / Rear	mm	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953	1013 / 953
Luggage Capacity	ltr	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170	350 / 450 - 1170
Fuel Tank Capacity	ltr	47	47	47	47	47	47	47	47	47
Curb Weight -acc DIN-	kg	1310 / 1385	1310 / 1385	1335 / 1410	1380 / 1455	1405 / 1480	1320 / 1395	1345 / 1420	1395 / 1470	1420 / 1495
Axle Load Ratio -unloaded DIN-	%	39.7	39.7	39.0	40.6	39.9	39.4	38.7	40.5	39.8
Gross Vehicle Weight / payload	kg	1780 / 470	1780 / 470	1805 / 470	1850 / 470	1875 / 470	1790 / 470	1815 / 470	1855 / 460	1880 / 460
Axle Load Limit Front / Rear	kg	995 / 850	985 / 850	1005 / 850	1010 / 890	1030 / 890	995 / 855	1015 / 855	1015 / 900	1035 / 900
Trailer Load Braked -12% / 8%-	kg	/	800 / 800	1200 / 1200	800 / 800	1200 / 1200	800 / 800	1200 / 1200	800 / 800	1200 / 1200
Trailer Load Unbraked / nose weight	kg	/	500 / 75	500 / 75	500 / 75	500 / 75	500 / 75	500 / 75	500 / 75	500 / 75
Gross vehicle weight -trailer towing-	kg		1855	1880	1925	1950	1865	1890	1930	1955
Rear axle load limit -trailer towing-	kg		959	959	999	999	959	959	997	997
Roof load	kg	75	75	75	75	75	75	75	75	75
Engine Type / Cylinders / Valves per Cylinder	-	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4	in line / 4 / 4
Fuel Management	-	DDE 7.01	DDE 7.01	DDE 7.2.1	DDE 7.01	DDE 7.2.1	DDE 7.01	DDE 7.01	DDE 7.01	DDE 7.01
Effective Displacement	cm ³	1598	1598	1995	1995	1995	1995	1995	1995	1995
Stroke / Bore	mm	83.6 / 78.0	83.6 / 78.0	90 / 84	83.6 / 78.0	90 / 84	90 / 84	90 / 84	90 / 84	90 / 84
Nominal Power Output / Engine Speed	hp (kW) / 1/min	90 (66) / 4000	112 (82) / 4000	112 (82) / 4000	112 (82) / 4000	112 (82) / 4000	143 (105) / 4000	143 (105) / 4000	143 (105) / 4000	143 (105) / 4000
Max Torque / Engine Speed	Nm / 1/min	215 / 1750-2500	270 / 1750-2250	270 / 1750-2250	270 / 1750-2250	270 / 1750-2250	305 / 1750-2700	305 / 1750-2700	305 / 1750-2700	305 / 1750-2700
Compression Ratio / Fuel Type	-	16.5 / DIESEL	16.5 / DIESEL	16.5 / DIESEL	16.5 / DIESEL	16.5 / DIESEL	16.5 / DIESEL	16.5 / DIESEL	16.5 / DIESEL	16.5 / DIESEL
Exhaust Emissions Classification	-	EUS	EUS	EUS	EUS	EUS	EUS	EUS	EUS	EUS
Gearbox Reference Code	-	G253 w TŮ	G253 w TŮ	AISIN F6 21	G253 w TŮ	AISIN F6 21	G253 TŮ	AISIN F6 21	G253 TŮ	AISIN F6 21
Gear Ratio 1st / 2nd / 3rd	-	3.308 / 1.87 / 1.194	3.308 / 1.87 / 1.194	4.044 / 2.371 / 1.556	3.308 / 1.87 / 1.194	4.044 / 2.371 / 1.556	2.308 / 1.213 / 1.483	4.044 / 2.371 / 1.556	2.308 / 1.213 / 1.483	4.044 / 2.371 / 1.556
Gear Ratio 4th / 5th / 6th	-	0.872 / 0.721 / 0.596	0.872 / 0.721 / 0.596	1.159 / 0.852 / 0.672	0.872 / 0.721 / 0.596	1.159 / 0.852 / 0.672	1.139 / 0.949 / 0.816	1.159 / 0.852 / 0.672	1.139 / 0.949 / 0.816	1.159 / 0.852 / 0.672
Reverse Ratio	-	3.231	3.231	3.193	3.231	3.193	3.231	3.193	3.231	3.193
Final Drive Ratio	-	3.706	3.706	3.683	3.706	3.683	3.706	3.683	3.706	3.683
Steering Type / Ratio	-	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1	EPS / 14.1
Brake Front / Diameter	- / mm	Ventilated Disc / 294	Ventilated Disc / 294	Ventilated Disc / 294	Ventilated Disc / 294	Ventilated Disc / 294	Ventilated Disc / 307	Ventilated Disc / 307	Ventilated Disc / 307	Ventilated Disc / 307
Brake Rear / Diameter	- / mm	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280	disc / 280
Drag Cd / A / Cd x A	- / m ² / m ²	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83
Top Speed	mph / km/h	106 / 170	115 / 185	112 / 180	112 / 180	109 / 175	123 / 198	121 / 195	121 / 195	120 / 193
Acceleration 0-62mph (0-100km/h)	s	12.9	11.3	11.3	11.3	11.8	9.3	9.5	9.5	9.5
Acceleration 0-1000m	s	34.8	32.6	33	33.1	33.5	30.5	30.7	30.8	30.9
Acceleration 50-75mph (80-120km/h) 4th / 5th	s	12.5 / 15.9	9.7 / 11.9	- / -	10.6 / 12.9	- / -	7.9 / 10.1	- / -	8.5 / 10.7	- / -
Output Per Litre	kW/ltr	41.3	51.3	41.1	51.3	41.1	52.6	52.6	52.6	52.6
Weight Ratio	kg/kW	19.8	16	16.3	16.8	17.1	12.6	12.8	13.3	13.5
Fuel Consumption -urban-	mpg / l/100km	60.1 / 4.7	60.1 / 4.7	59.2 / 7.2	53.3 / 5.3	53.7 / 7.6	54.3 / 5.2	38.7 / 7.3	53.3 / 5.3	56.7 / 7.7
Fuel Consumption -extra urban-	mpg / l/100km	67.3 / 4.2	67.3 / 4.2	60.1 / 4.7	60.1 / 4.7	56.5 / 5.0	65.9 / 4.8	60.1 / 4.7	60.1 / 4.7	55.4 / 5.1
Fuel Consumption -combined-	mpg / l/100km	64.2 / 4.4	64.2 / 4.4	50.4 / 5.6	57.6 / 4.9	47.1 / 6.0	61.4 / 4.6	49.6 / 5.7	57.6 / 4.9	46.3 / 6.1
Range at Fuel Consumption-combined-	miles / km	665 / 1070	665 / 1070	522 / 840	597 / 960	488 / 785	634 / 1020	513 / 825	597 / 960	478 / 770
CO ₂ Emissions -EU-	g/km	115	115	149	129	158	122	150	130	160
Tyre Size -front-	-	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V
Tyre Size -rear-	-	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/60 R16 92H	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V	205/55 R17 91V
Wheel Size -front-	-	6.5J x 16 Steel Wheel	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy
Wheel Size -rear-	-	6.5J x 16 Steel Wheel	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	6.5J x 16 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy	7J x 17 Light Alloy
Radiator Incl. Heater Capacity	ltr	5.4	5.4	5.4	5.4	5.4	5.2	5.2	5.2	5.2
Engine Oil Replacement Capacity	ltr	5.2	5.2	5.2	5.2	5.2	5.2	5.2	5.2	5.2
Gearbox Fluid Replacement Capacity	ltr	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent	permanent
Battery Capacity / Installed Position	Ah / -	70 / Engine Bay	70 / Engine Bay	70 / Engine Bay	70 / Engine Bay	70 / Engine Bay	70 / Engine Bay	70 / Engine Bay	70 / Engine Bay	70 / Engine Bay
Alternator Output rating	A/W	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100	150 / 2100