## **BMW** of North America, Inc.

For Release IMMEDIATE

Contact Robert D. Mitchell

Product Information Manager Product Information Specialist

201-307-3790 / e-mail: rob.mitchell@bmwna.com 201-307-3789 / e-mail: dave.buchko@bmwna.com

## 2000 BMW 7 SERIES SPECIFICATIONS

Dave Buchko

**Bold** indicates new specification for 2000

|                                    | 740i              | 740iL     | 740iL<br>Protection | 750iL     | 750iL<br>Protection |
|------------------------------------|-------------------|-----------|---------------------|-----------|---------------------|
| GENERAL                            |                   |           |                     |           |                     |
| Curb weight, lb.                   | 4255              | 4288      | 4630                | 4597      | 4905                |
| Weight distribution, front/rear, % | 50.8/49.2         | 50.6/49.4 | 49.8/50.2           | 50.1/49.9 | 49.4/50.6           |
| Wheelbase, in.                     | 115.4             | 120.9     | 120.9               | 120.9     | 120.9               |
| Track, front/rear, in.             | 60.9/61.512       |           |                     |           |                     |
| Length, in.                        | 196.2             | 201.7     | 201.7               | 201.7     | 201.7               |
| Width, in.                         | 73.3 <sup>1</sup> |           |                     |           |                     |
| Height, in.                        | 56.5 <sup>2</sup> | 56.1      | 56.1                | 56.1      | 56.1                |

<sup>&</sup>lt;sup>1</sup> Specification applies to all models

<sup>&</sup>lt;sup>2</sup> With optional Sports Package on 740i, tracks f/r are 61.1/61.6 in., height is 56.3 in.

|  | 740i                   | 740iL                                     | 740iL      | 750iL     | 750iL      |  |
|--|------------------------|---|------------|-----------|------------|--|
| ACCOMMODATIONS                         |                        |   | Protection |           | Protection |  |
| Seating capacity, persons              | 5                      | 5   | 4          | 5         | 4          |  |
| Shoulder room, front/rear, in.         | 58.4/58.4 <sup>1</sup> |   |            |           |            |  |
| Head room, front/rear, in.             | 37.4/37.9              | 37.5/38.1                                 | 38.9/38.2  | 37.5/38.1 | 38.9/38.2  |  |
| Leg room, front/rear, in.              | 41.9/36.7              | 41.9/41.9                                 | 41.9/41.9  | 41.9/41.9 | 41.9/41.9  |  |
| EPA interior volume, cu ft.            | 100.3                  | 107.0                                     | 107.0      | 107.0     | 107.0      |  |
| EPA cargo volume, cu ft.               | 13.0 <sup>1</sup>      |   |            |           |            |  |
|  |                        |   |            |           |            |  |
| BODY                                   |                        |   |            |           |            |  |
| Туре                                   | Unitized all-ste       | Unitized all-steel structure <sup>1</sup> |            |           |            |  |
| Aerodynamic drag coefficient ( $C_D$ ) | 0.31                   | 0.31                                      | 0.31       | 0.32      |            |  |
| 0.32                                   |                        |   |            |           |            |  |
| EPA size classification                | Large <sup>1</sup>     |   |            |           |            |  |

<sup>1</sup> Specification applies to all models

|                           | 740i                  | 740iL   | <b>740iL</b><br>Protection | 750iL | 750iL<br>Protection                                |  |
|---------------------------|-----------------------|---|----------------------------|-------|--|--|
| ENGINE & ELECTRICAL       |                       |   |                            |       |  |  |
| Engine type               | DOHC 32-v             | DOHC 32-valve (4-cam) V-8, VANOS <sup>3</sup>         |                            |       | SOHC V-12  |  |
|                           | steplessly v          | ariable valve tin                                     | ning                       |       |  |  |
| Bore x stroke, in.        | 3.62 x 3.26           |   | 3.35 x 3.11                |       |  |  |
| mm                        | 92.0 x 82.7           |   | 85.0 x 79.0                |       |  |  |
| Displacement, cu in./cc   | 268/4398              |   | 328/5379                   |       |  |  |
| Compression ratio         | 10.0:1 <sup>1</sup>   | 10.0:1 <sup>1</sup>                                   |                            |       |  |  |
| Power @ rpm, hp           | 282 @ 5400            | )   | 326 @ 5000                 |       |  |  |
| Torque @ rpm, lb-ft.      | 324 @ 3700            | 324 @ 3700  |                            |       |  |  |
| Engine-management system  |                       | Bosch HFM-Motronic M5.2.1 with adaptive knock control |                            |       | Bosch HFM-Motronic M5.2.1 (dual DME) with adaptive |  |
| Fuel requirement          | Premium ur            | Premium unleaded <sup>1</sup>                         |                            |       | I  |  |
| Fuel capacity, U.S. gal.  | 22.5 <sup>4</sup>     | 22.5 4  | 22.5 <sup>4</sup>          | 25.1  | 25.1   |  |
| Battery capacity, amp-hr. | 110 <sup>1</sup>      |   |                            |       |  |  |
| Alternator output, amp./W | 150/2100 <sup>1</sup> |   |                            |       |  |  |
|                           |                       |   |                            |       |  |  |

<sup>&</sup>lt;sup>3</sup> VANOS = **Va**riable **No**ckenwellen **S**teuerung = variable cam control, or variable valve timing 

<sup>1</sup> Specification applies to all models

<sup>4</sup> With optional Adaptive Ride Package, 25.1 U.S. gal.

-4-

|                         | 740i   | 740iL                       | 740iL<br>Protection   | 750iL          | 750iL<br>Protection   |
|-------------------------|--|-----------------------------|-----------------------|----------------|-----------------------|
| DRIVETRAIN              |  |                             |                       |                |                       |
| Drive system            | Front engine/re  | ear drive <sup>1</sup>      |                       |                |                       |
| Automatic transmission  | ZF 5HP24 EH  | <sup>5</sup> , ZF 5HP24 EH, | ZF 5HP24 EH,          | ZF 5HP30 EH,   | ZF 5HP30 EH,          |
|                         | 5-speed  | 5-speed                     | 5-speed               | 5-speed        | 5-speed               |
| Ratios: 1st             | 3.57:1   | 3.57:1                      | 3.57:1                | 3.55:1         | 3.55:1                |
| 2nd                     | 2.20:1   | 2.20:1                      | 2.20:1                | 2.24:1         | 2.24:1                |
| 3rd                     | 1.51:1   | 1.51:1                      | 1.51:1                | 1.54:1         | 1.54:1                |
| 4th                     | 1.00:1   | 1.00:1                      | 1.00:1                | 1.00:1         | 1.00:1                |
| 5th                     | 0.80:1   | 0.80:1                      | 0.80:1                | 0.79:1         | 0.79:1                |
| Reverse                 | 4.10:1   | 4.10:1                      | 4.10:1                | 3.68:1         | 3.68:1                |
| Final drive ratio       | 2.93:15  | 2.93:1                      | 2.93:1                | 2.81:1         | 2.81:1                |
| CHASSIS                 |  |                             |                       |                |                       |
| Body/frame construction | Unitized steel   | Unitized steel              | Unitized steel        | Unitized steel | Unitized steel        |
|                         |  |                             | with Aramide<br>armor |                | with Aramide<br>armor |
| Front Suspension        | Struts, forged aluminum double pivot lower arms, variable diameter coil springs, twin tube gas-pressure shock absorbers, anti-roll bar <sup>1</sup> 740i with Sport Package: sport calibration |                             |                       |                |                       |

<sup>&</sup>lt;sup>1</sup> Specification applies to all models
<sup>5</sup> With optional Sports Package, 740i transmission has STEPTRONIC and a high-stall-speed torque converter, final drive ratio is 3.15:1

|                                    | 740i   | 740iL   | <b>740iL</b><br>Protection | 750iL              | 750iL<br>Protection        |  |  |
|------------------------------------|--|---|----------------------------|--------------------|----------------------------|--|--|
| CHASSIS (cont'd)                   |  |   |                            |                    |                            |  |  |
| Rear suspension                    | 4-link integral  | suspension, coil  | springs, twin-tube         | e gas-pressure sho | ock absorbers <sup>1</sup> |  |  |
|                                    | 740i with Spor   | t Pkg.: sport cal   | libration                  |                    |                            |  |  |
| Adaptive Ride Package              | Electronic Damping Control, self-leveling rear suspension & rear anti-roll bar - |   |                            |                    |                            |  |  |
|                                    | opt. 740i & 74   | 0iL; std. 740iL P   | rotection, 750iL &         | 750iL Protection;  |                            |  |  |
|                                    | Not Available  | Not Available on with 740i Sport Package                                |                            |                    |                            |  |  |
| Steering type                      | Self-adjusting   | Self-adjusting recirculating ball, vehicle-speed-sensitive power assist |                            |                    |                            |  |  |
| Overall ratio                      | 16.9:1 <sup>1</sup>  |   |                            |                    |                            |  |  |
| Turns lock-to-lock                 | 3.7 1  |   |                            |                    |                            |  |  |
| Turning circle, ft. (curb-to-curb) | 38.1   | 40.0  | 40.0                       | 40.0               | 40.0                       |  |  |
| Antilock braking system:           |  |   |                            |                    |                            |  |  |
| Front discs                        | 12.8-in. vented  | d   |                            | 13.1-in. vented    |                            |  |  |
| Rear discs                         | 12.8-in. solid   |   |                            | 12.9-in. vented    |                            |  |  |
| Assist                             | Vacuum <sup>1</sup>  |   |                            |                    |                            |  |  |
| Wheels: standard                   | Cast alloy   |   | Cast alloy                 | Cast alloy         | Cast alloy                 |  |  |
|                                    | 16 x 8.0   |   | 17 x 8.0                   | 16 x 7.5           | 17 x 8.                    |  |  |
|                                    | optional cast alloy, 18 x 8.0 F/ 18 x 9.5 °                                      |   |                            |                    |                            |  |  |

<sup>&</sup>lt;sup>1</sup> Specification applies to all models <sup>6</sup> Included as part of the Sport Package on the 740i or as a stand alone optional on all but the Protection Line models

|          |                                    | 740i   | 740iL | 740iL                   | 750iL                      | 750iL                   |  |
|----------|------------------------------------|--|-------|-------------------------|----------------------------|-------------------------|--|
| CHASS    | SIS (cont.)                        |  |       | Protection              |                            | Protection              |  |
| Tires:   | standard                           | 235/60R-16 H<br>all-season                             |       | 235/55R-17H<br>run-flat | 235/60R-16 H<br>all-season | 235/55R-17H<br>run-flat |  |
|          | optional                           | 235/50ZR-18 F / 255/45ZR-18 R performance <sup>6</sup> |       |                         |                            |                         |  |
| PERFO    | RMANCE                             |  |       |                         |                            |                         |  |
| Accelera | ation, 0-60 mph, sec. <sup>7</sup> | 6.98   | 6.9   | 7.4                     | 6.6                        | 7.1                     |  |
| Top spe  | eed, mph                           | 128 <sup>9</sup>                                       |       |                         |                            |                         |  |
| EPA est  | . MPG, city/highway                | 17/23 <sup>10</sup>                                    | 17/23 | 17/23                   | 13/20                      | 13/20                   |  |

11/24/99

-

<sup>&</sup>lt;sup>6</sup> Included as part of the Sport Package on the 740i or as a stand alone optional on all but the Protection Line models

<sup>&</sup>lt;sup>7</sup> BMW AG test data. Actual acceleration results may vary depending upon vehicle specification, road & environmental conditions, test procedures and driving style. These results should be used for comparison only duplication should not be attempted on public roads. BMW encourages you to obey all posted speed limits and wear your seat belt at all times.

<sup>&</sup>lt;sup>8</sup> 6.8 with Sport Package

<sup>&</sup>lt;sup>9</sup> Electronically limited on all models. On 740i with Sport Package top speed limited to 155 mph

<sup>&</sup>lt;sup>10</sup> 15/21 with Sport Package