

BMW

U.S. Media Information

Contacts:

Thomas Plucinsky
Product & Technology Communications Manager
201-307-3783 / thomas.plucinsky@bmwna.com

Dave J. Buchko
Advanced Powertrain & Heritage Communications
201-307-3709 / dave.buchko@bmwna.com

Matthew Russell
BMW Product & Technology Communications
Tel. 201 307 3755
Matthew.Russell@bmwna.com

Technical Data.

2010 BMW 3 Series Sports Wagon.

		328i Sports Wagon Manual 6 Speed	328i Sports Wagon Auto 6 Speed	328i xDrive Sports Wagon Manual 6 Speed	328i xDrive Sports Wagon Auto 6 Speed
10.23.2009					
Body					
No. of Doors / Seating Capacity	-	5 / 5	5 / 5	5 / 5	5 / 5
Vehicle Length	mm / inch	4537 / 178.6	4537 / 178.6	4537 / 178.6	4537 / 178.6
Vehicle Width	mm / inch	1817 / 71.5	1817 / 71.5	1817 / 71.5	1817 / 71.5
Vehicle Height, Unloaded	mm / inch	1418 / 55.8	1418 / 55.8	1418 / 55.8	1418 / 55.8
Wheelbase	mm / inch	2760 / 108.7	2760 / 108.7	2760 / 108.7	2760 / 108.7
Turning Circle	m / ft	11 / 36.1	11 / 36.1	11.8 / 38.7	11.8 / 38.7
Track, Front	mm / inch	1500 / 59.1	1500 / 59.1	1500 / 59.1	1500 / 59.1
Track, Rear	mm / inch	1529 / 60.2	1529 / 60.2	1529 / 60.2	1529 / 60.2
Width at Shoulderheight, Front	mm / inch	1408 / 55.4	1408 / 55.4	1408 / 55.4	1408 / 55.4
Width at Shoulderheight, Rear	mm / inch	1400 / 55.1	1400 / 55.1	1400 / 55.1	1400 / 55.1
Effective Leg Room, Front	mm / inch	1045 / 41.1	1045 / 41.1	1045 / 41.1	1045 / 41.1
Effective Leg Room, Rear	mm / inch	878 / 34.6	878 / 34.6	878 / 34.6	878 / 34.6
Effective Head Room, Front	mm / inch	978 / 38.5	978 / 38.5	978 / 38.5	978 / 38.5
Effective Head Room, Rear	mm / inch	964 / 38	964 / 38	964 / 38	964 / 38
Trunk Volume acc SAE1100	ft³	25	25	25	25
Fuel Capacity	L / gal	61 / 16.1	61 / 16.1	61 / 16.1	61 / 16.1
Curb Weight	kg / lbs	1600 / 3527	1630 / 3594	1710 / 3770	1730 / 3814
Weight Distribution Front/Rear	%	48.4 / 51.6	48.8 / 51.2	50.9 / 49.1	51.2 / 48.8
Gross Vehicle Weight Rating (GVWR)	kg / lbs	2100 / 4630	2130 / 4696	2210 / 4872	2230 / 4916
Payload	kg / lbs				
Axle Load Limit, front	kg / lbs	965 / 2127	965 / 2127	1055 / 2326	1055 / 2326
Axle Load Limit, rear	kg / lbs	1200 / 2646	1200 / 2646	1200 / 2646	1200 / 2646
Towing Capacity	kg / lbs	-	-	-	-
Roof Load Limit	kg / lbs	75 / 165	75 / 165	75 / 165	75 / 165
Drag Coefficient	Cd	0.3	0.3	0.31	0.31
Drag Cd x A	m² / ft²	0.65 / 6.99	0.65 / 6.99	0.67 / 7.21	0.67 / 7.21
Engine					
Engine Type / Cylinder / Valves per Cylinder	-	Inline / 6 / 4 VANOS	Inline / 6 / 4 VANOS	Inline / 6 / 4 VANOS	Inline / 6 / 4 VANOS
Engine Management System	-	MSV80 Port Injection	MSV80 Port Injection	MSV80 Port Injection	MSV80 Port Injection
Induction System		Natural VALVETRONIC	Natural VALVETRONIC	Natural VALVETRONIC	Natural VALVETRONIC
Displacement	cm³ / inch³	2996 / 182.8	2996 / 182.8	2996 / 182.8	2996 / 182.8
Stroke	mm / inch	88 / 3.46	88 / 3.46	88 / 3.46	88 / 3.46
Bore	mm / inch	85 / 3.35	85 / 3.35	85 / 3.35	85 / 3.35
Power	SAE hp / rpm	230 / 6500	230 / 6500	230 / 6500	230 / 6500
Torque	ft lbs / rpm	200 (270) / 2750	200 (270) / 2750	200 (270) / 2750	200 (270) / 2750
Compression Ratio / Fuel type	-	10.7 / Premium	10.7 / Premium	10.7 / Premium	10.7 / Premium
Chassis and Suspension					
Codification of Reference Gearbox	-	I	GM6	H	GM6
Gear Ratios I	-	4.323	4.065	4.35	4.065
II	-	2.456	2.371	2.496	2.371
III	-	1.659	1.551	1.665	1.551
IV	-	1.23	1.2	1.23	1.2
V	-	1	0.853	1	0.853
VI	-	0.848	0.674	0.851	0.674
Reverse Ratio	-	3.938	3.2	3.926	3.2
Final Drive Ratio	-	3.23	3.73	3.38	3.91
Steering Type / Ratio	-	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 18.2	Rack-and-pinion / 18.2
Front Brakes / Diameter	- / mm / inch	Vent. Disc / 312 / 12.3	Vent. Disc / 312 / 12.3	Vent. Disc / 312 / 12.3	Vent. Disc / 312 / 12.3
Rear Brakes / Diameter	- / mm / inch	Vent. Disc / 300 / 11.8	Vent. Disc / 300 / 11.8	Vent. Disc / 300 / 11.8	Vent. Disc / 300 / 11.8
Tire Type, Front	-	205/55 R16 91H RSC AS	205/55 R16 91H RSC AS	205/55 R16 91H RSC AS	205/55 R16 91H RSC AS
Tire Type, Rear	-	205/55 R16 91H RSC AS	205/55 R16 91H RSC AS	205/55 R16 91H RSC AS	205/55 R16 91H RSC AS
Wheels, Front	-	7J x 16 Light alloy	7J x 16 Light alloy	7J x 16 Light alloy	7J x 16 Light alloy
Wheels, Rear	-	7J x 16 Light alloy	7J x 16 Light alloy	7J x 16 Light alloy	7J x 16 Light alloy
Performance					
Top Speed	km/h / mph	210 / 130	210 / 130	210 / 130	210 / 130
Top speed w. Sport Package	km/h / mph	240 / 150	240 / 150	238 / 148	236 / 147
Acceleration, 0-60 mph	s	6.5	7.1	7.1	7.3
Acceleration, 0-100 Km/h	s	6.9	7.5	7.4	7.7
Fuel Economy, EPA Estimate - City	mpg	17	18	17	17
Fuel Economy, EPA Estimate - Highway	mpg	26	27	25	25
Fuel Economy, EPA Estimate - Combined	mpg	20	21	20	20
Approximate Range	km / miles	715 / 450	745 / 460	655 / 405	670 / 415